



CORTEC
CORPORATION

Environmentally Safe VpCI®/MCI® Technologies

Desicorr® VpCI® Pouches/ Desicorr® NW VpCI®

DESCRIPTION

Desicorr® VpCI® is a specially designed, two-sided pouch containing a unique combination of desiccant and Vapor phase Corrosion Inhibitor (VpCI®) Technology. Desicorr® VpCI® Pouches are ideal for protecting packaged ferrous and non-ferrous metals from corrosion for up to two years.

Unlike conventional desiccants, the dual function of the Desicorr® VpCI® Pouches reduces moisture in the air (desiccant action) and provides multi-metal protection (VpCI® action) within a package. In essence, the desiccant action allows the VpCI® to have free access to the surface of the metal, without competition from moisture on the metal surface.

Desicorr® VpCI® Pouches are available in both windowed and non-windowed versions (NW). The windowed version contains some indicator spheres that will change color from yellow to green when the desiccant is fully spent.


PACKAGING & STORAGE

Desicorr® VpCI® Pouches are available in cartons of 300 units.

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years

HIGH PERFORMANCE VpCI® PACKAGING



FEATURES

- Available in 1/6 Unit, 1 Unit sizes
- Non-windowed (NW) versions also available in 4 Unit and 8 Unit sizes
- Protective VpCI® film does not need removal
- Commercially equivalent to MIL-D-3464E, Type I & Type II
- VpCI® is self-replenishing to provide continuous protection if package is opened and resealed
- Can be easily inserted into package manually or automatically

BENEFITS

- Synergistic action between desiccant and VpCI® gives unparalleled corrosion protection
- VpCI® continues to provide corrosion protection even when desiccant is fully spent
- VpCI® action protects recessed and inaccessible surfaces
- No degreasing or cleaning of protected part required
- Multi-metal protection

METALS PROTECTED

- Aluminum
- Carbon Steel
- Stainless Steel
- Copper
- Brass
- Galvanized Steel
- Silicon Steel
- Solder

Desicorr® VpCl® Pouches/ Desicorr® NW VpCl®

APPLICATION

Desicorr® VpCl® is designed to protect products, components, or assemblies when packaged in corrugated boxes, plastic wrap or bags, and wood or metal containers.


Successful usages include:

- Completed assemblies, parts, and components
- Motors
- Mechanical controls
- Precision machined or stamped parts
- Marine and commercial electronic equipment
- Electrical equipment
- Tools

To apply, manually or automatically insert a Desicorr® VpCl® Pouch into the space needing protection. Then immediately close or seal the container. **Note:** Desicorr® VpCl® Pouches must be used immediately after removing from barrier bag, and the barrier bag must be resealed immediately after removing pouches.

TYPICAL PROPERTIES

Water Absorption Capacity Of Desicorr® VpCl®



Unit Size	Protected Volume	Pouch Dimensions	Moisture Absorption Capacity (g) at 77 °F (25 °C), 75% R.H.
1/6	1 ft ³ (28 L)	2.75" x 2.5" x 0.125" (7 cm x 6.4 cm x 0.6 cm)	1.32
1	5 ft ³ (140 L)	7" x 4" x 0.125" (17.8 cm x 10.2 cm x 0.6 cm)	9.9
4 (Non-windowed only)	20 ft ³ (560 L)	6" x 8" x 0.75" (15 cm x 20 cm x 2 cm)	39.6
8 (Non-windowed only)	40 ft ³ (1120 L)	6" x 12" x 0.75" (15 cm x 30 cm x 2 cm)	79.2

4119 White Bear Parkway, St. Paul, MN 55110 USA
 Phone (651) 429-1100, Fax (651) 429-1122
 Toll Free (800) 4-CORTEC
 info@cortecvci.com
<https://www.cortecvci.com>
<https://www.cortecpackaging.com>



LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.